

Neonatal Transport Incubator



NICU



L&D

Meets NRP guidelines
Integrated shock absorbers
Compact and easy to maneuver
Built in phototherapy*

*Optional

Technical Specifications

Standard Features	Large double-wall chamber with 360° visibility Head and front access doors 2 hand ports on front door 2 hand ports on back of infant chamber 5 access ports for IV / respiratory tubing Slide out intubation tray High intensity exam light with LED light bar Extended life battery	Skin temperature probe Large LED display Humidification reservoir IV pole 2 pairs of infant positioning straps Power cord wrap Cylinder mounts Pressure diffusing mattress
Audible and Visual Alarms	System failure Temp sensor failure Air flow failure AC failure	Power failure High temp Low battery
Visual Indicators	Set air temp Set temp >37°C Air temp Baby temp Battery life	Battery power Battery charging AC power External DC power
Dimensions	19.5 in H x 22 in W x 50 in L (w/o cart, IV pole, or exam light)	
Weight	94 lbs (w/o cart, IV pole, or exam light)	
AC Power	120V AC, 50-400 Hz	
External DC Power	12V DC input, 10A maximum	
Internal Battery	One 12V 26 amp-hour sealed lead acid gel type with automatic recharge	
Digital Air Temperature Control	17.0°C to 38.9°C range, 0.1°C increments	Display resolution 0.1°C
Sound Level	<60 dB	
Additional Options Available		
Integrated Pulse Oximetry	Masimo® or Nellcor™, and O ₂ analyzer with audible and visual alarms	
Airway Management	Air and O ₂ inputs (DISS) O ₂ blender (no bleed / low flow) Flowmeter (0 to 16 L/min)	Air and O ₂ regulators with quick connection Air and O ₂ supply hoses
Conventional Ventilator	Neonatal transport ventilator with remote vent outputs	
Electric Suction	Portable, battery-powered suction	
Patient Monitor	Install hospital-supplied monitor or one provided by International Biomedical	
Thermal Privacy Cover	Provides patient privacy	Protects from external influences
Resuscitation	Puffin Infant Resuscitator	T-piece resuscitation and bag & mask
Shelves / Mounts	Overhead shelf and / or side platforms	Mounting posts 1 in diameter x 5 in, or 1 in x 7.5 in
Phototherapy	Average intensity 15 µw/cm ² /nm, 450 nm wavelength	
Mobile Cart	2 storage shelves Bottom shelf with privacy doors (additional option) Large 5 inch locking casters 4 shock absorbers	

Europe

International Biomedical AG

Glütschbachstrasse 100, CH-3661 Uetendorf, Switzerland
T. +41.33.345.66.00 F. +41.33.345.66.08
welcome@int-bio.ch

Worldwide

International Biomedical

8206 Cross Park Drive, Austin, Texas USA 78754
T. 512.873.0033 F. 512.873.9090
sales@int-bio.com

int-bio.com

International Biomedical reserves the right to make changes in specifications and features shown herein or discontinue the product described at any time without notice or obligation. Contact your representative for the most current information.



IB A750i - 10/2019